

NXT-I

Technical specs

Type of fuel	Wood
Recommended surface	1050 to 2000 sq. ft.
Maximum output - EPA test wood	29400 BTU
Maximum output - seasoned cord wood	80000 BTU
Color	Metallic black
Exterior dimensions	25"W x 29"D x 33½"H
Exhaust pipe diameter	6"
Type of chimney	2100° F / 650° C
Recommended chimney diameter	6"
Minimum chimney height	12' (3,66 m)
Firebox dimensions	17"W x 19¼"D
Log positioning	Depth
Maximum log length	18"
Door opening dimensions	15½"W x 9¾"H
Type of door	Glass with cast iron frame

Minimum clearances to combustibles

(Data expressed in inches. 1 inch = 25.4 mm)

	Canada		USA	
	Single walled pipe	Double walled pipe	Single walled pipe	Double walled pipe
Back	14"	6"	14"	6"
Sides	14"	12"	14"	12"
Corners	7"	6"	7"	6"
Top*	84"	84"	84"	84"
* Measured from floor.				

Glass surface

14½"L x 10¼"H

Steel thickness

5/16"

Weight

420 lbs (191 kg)

Warranty

Limited lifetime

Test standard - safety

ULC S-627, UL 1482

Test standard - emissions

EPA Method 28