

Technical specs

Type of fuel	Wood
Recommended surface	550 to 1500 sq. ft.
Maximum output - EPA test wood	47100 BTU
Maximum output - seasoned cord wood	55000 BTU
Color	Metallic black
Exterior dimensions	22¼"W x 22¾"D x 30¼"H
Exhaust pipe diameter	6"
Type of chimney	2100° F / 650° C
Recommended chimney diameter	6"
Minimum chimney height	12' (3,66 m)
Firebox dimensions	18¼"W x 14"D
Log positioning	Width
Maximum log length	16"
Door opening dimensions	16"W x 8¼"H
Type of door	Glass with cast iron frame

Minimum clearances to combustibles

(Data expressed in inches. 1 inch = 25.4 mm)

	Canada		USA	
	Single walled pipe	Double walled pipe	Single walled pipe	Double walled pipe
Back	17"	12"	17"	12"
Sides	15"	12"	15"	12"
Corners	10"	7"	10"	7"
Top*	84"	84"	84"	84"

* Measured from floor.

Glass surface

13¾"W x 7¾"H

Steel thickness

¼"

Weight

288 lbs (131 kg)

Warranty

Limited lifetime

Test standard - safety

ULC S-627, UL 1482

Test standard - emissions

EPA Method 28