

Technical specs

Type of fuel	Wood
Recommended surface	850 to 1600 sq. ft.
Maximum output - EPA test wood	34000 BTU
Maximum output - seasoned cord wood	60000 BTU
Color	Metallic black
Exterior dimensions	25½"W x 22¾"D x 29¾"H
Exhaust pipe diameter	6"
Type of chimney	2100° F / 650° C
Recommended chimney diameter	6"
Minimum chimney height	12' (3,66 m)
Firebox dimensions	21¼"W x 14"P
Log positioning	Width
Maximum log length	18"
Door opening dimensions	17¾"W x 8¼"H
Type of door	Glass with cast iron frame

Minimum clearances to combustibles

(Data expressed in inches. 1 inch = 25.4 mm)

	Canada		USA	
	Single walled pipe	Double walled pipe	Single walled pipe	Double walled pipe
Back	14"	6"	14"	6"
Sides	12"	11"	12"	11"
Corners	7"	5"	7"	5"
Top*	84"	84"	84"	84"

* Measured from floor.

Glass surface

16"W x 7³/₄"H

Steel thickness

1/4"

Weight

322 lbs (147 kg)

Warranty

Limited lifetime

Test standard - safety

ULC S-627, UL 1482

Test standard - emissions

EPA Method 28