

Technical specs

Type of fuel	Wood
Recommended surface	1050 to 1900 sq. ft.
Maximum output - EPA test wood	38700 BTU
Maximum output - seasoned cord wood	75000 BTU
Color	Metallic black
Exterior dimensions	25½"W x 25¾"D x 30¾"H
Exhaust pipe diameter	6"
Type of chimney	2100° F / 650° C
Recommended chimney diameter	6"
Minimum chimney height	12' (3,66 m)
Firebox dimensions	21¼"W x 16¾"D
Log positioning	Width
Maximum log length	20"
Door opening dimensions	17¾"W x 9"H
Type of door	Glass with cast iron frame

Minimum clearances to combustibles

(Data expressed in inches. 1 inch = 25.4 mm)

	Canada		USA	
	Single walled pipe	Double walled pipe	Single walled pipe	Double walled pipe
Back	14"	6"	14"	
Sides	12"	12"	12"	12"
Corners	7"	5"	7"	5"
Top*	84"	84"	84"	84"
* Measured from floor.				

Glass surface	16¼"W x 9½"H
Steel thickness	5/16"
Weight	395 lbs (180 kg)
Warranty	Limited lifetime
Test standard - safety	ULC S-627, UL 1482
Test standard - emissions	EPA Method 28